

MÖDT

All-in-One in-store Digital Signage Solution

WarmTOUCH WT22M-RH



- Easy to install All-in-One solution
- Multi Touch panel designed for customer interaction
 - 4-wire resistive, driver supports 10 points
- Robust structure design can be installed without customization
- Symmetrical display to switch the monitor between portrait or landscape mode
 - Default resolution: 21.5 inch (1920x1080)
 - Dimensions 532x332x60 mm (WxHxD)
- Socket G2 Intel Sandy Bridge CPU support
- AOpen Silent Tek Thermal Module, low noise (24dB idle mode)
- IP54 panel dust prevention with Slim Bezel Design
- Ventilation/thermal design for long-time use
- Easy to clean, because of its frameless design
- All function keys supported with security lock
- Watchdog Timer (1sec-255min)
- Capable of supporting additional LCD monitor VGA output for dual screen



Specifications

Dimensions(mm)	532x332x60mm(WxHxD)
Weight	9Kg / 19.84 lbs
CPU	Supports Socket G2 Intel Sandy Bridge CPU 1066/1333 MHz
CPU Thermal	AOpen Silent Tek Thermal Module Noise 24dB (idle mode)
Chipset	Intel QM67
Memory	Dual Channel DDRIII SO-DIMM x 2 1066/1333MHz Max Memory :4G
Graphics	CPU build-in VGA Output x 1 VGA Input(Monitor) x 1
LAN	Dual Intel Gigabit Ethernet 10/100/1000
Audio	Realtek HD Audio Codec ALC886 5.1 Channel
Expansion slot	mini card Slot x 2
Storage	5-ATA Connector x 1 (for 2.5" HDD)
LCD (LED Back light)	Default Resolution : 21.5"(1920x1080) Maximum Brightness : 250nits
Touch Panel	Multi Touch 4-Wire Resistive, driver support 10 points
Aspect Ratio	16:9
Button / Indicator	Power Button , Monitor Function Buttons, HDD Indicator (blue) x 1 Power indicator (blue) x 1
System I/O	DC 19V/20V Jack x 1 VGA In Port (Monitor) x 1 RS232 Port (Monitor) x 2 VGA Out Port x 1 (Duplex and External Mode) RJ45 LAN Jack x 2 USB 2.0 x 6 PC Legacy RS232 Serial Port (COM Port) (RI/SV/12 by Jumper Setting) x4 RS485 or RS422 (COM2 by Jumper Setting) x 1 RJ11 for Cash Drawer (12V/20V by Jumper) x 1 PC Legacy Printer Port x1 Audio Line-in x 1, Line-out x 1, Mic-in x 1 Upgrade for Antenna Port x 3 Kensington Lock Hole x 1
Webcam	1.3 MP x 1
Mic	High Sensitivity Mic x 1
Mount Kit	Wall Mount kit x 1
Adapter	90W (20V, 4.5A) AC Adapter
Watchdog Timer	1sec ~255min
Accessories	90W PWR Adapter x 1 Power Cord x 1 Utilities & Drivers CD x 1 EIG x 1

* AOpen reserves the right to revise all the specifications and information contained in this document, which are subject to change without prior notice.